

BUSH HOG®



*Performance
You Can
Count
On™*

FINISH MOWERS

HDTH SERIES | HDTH5, HDTH6, HDTH7, HDTH8



HDTH SERIES FINISH MOWERS

Bush Hog® HDTH “Turf Hog” Finish Mower

Turn your tractor into a lawn mowing machine with the new HDTH “Turf Hog” Finish Mowers from Bush Hog®. These new Finish Mowers deliver superior grass cutting performance for your well-kept lawn. With models ranging from 5’ - 8’, our HDTH Finish Mowers help you save time spent cutting your lawn, and more time enjoying it. Built Bush Hog® tough in Selma, AL, our new HDTH Finish Mowers are manufactured to the highest quality standards for durability and performance.

Powerful but smooth even in the toughest grasses!

- 1 Year Limited Warranty with a 5 Year Gearbox Warranty
- 60-99 inch Cutting Widths
- Minimum Required HP of 15-35 to meet the needs of today’s smaller, compact tractors
- Quick Hitch compatibility on all models allows for easier hook up
- Dual floating hitch points allow the mower to rise and fall with the contour of terrain
- Blade Tip Speeds over 18,200 feet per minute ensure a clean cut every time
- 1-1/2” blade overlap eliminates streaking
- Cutting height adjustment is made with the pull of a pin, and ranges from 1-1/2” to 6-1/2”
- New dove-tail rear discharge design steadily slopes downward eliminating the need for any type of chain shielding, thereby reducing the possibility of clumping or thrown objects
- Durable 7 gauge steel decks
- Sideband depth increased to 5” to allow additional flow of cut material under deck reducing clipping size



- Greasing blade spindles and idlers is easy with openings in deck
- Adjustable Spring-Loaded Idlers maintain proper belt tension
- Axle arms are offset to reduce grass compaction and tire tracking
- Strong Aramid fiber belts reduce stretching
- Spring-style lynch pins prevent accidental snags keeping casters locked in place

SPECIFICATIONS

Model	HDTH5	HDTH6	HDTH7	HDTH8
Cutting Width	60"	72"	84"	99"
Cutting Height (1/2" increments)	1-1/2" - 6-1/2"	1-1/2" - 6-1/2"	1-1/2" - 6-1/2"	1-1/2" - 6-1/2"
Tractor HP Range	15-35 PTO	20-40 PTO	30-55 PTO	35-55 PTO
Hitch Type	Cat 1 Std & QH	Cat 1 Std & QH	Cat 1, Cat 2 Std & QH	Cat 1, Cat 2 Std & QH
Blade Size	1/4" x 2-1/2" x 21"	1/4" x 2-1/2" x 25"	5/16" x 2-1/2" x 29"	1/4" x 2-1/2" x 21"
Number of Blades	3	3	3	5
Blade Tip Speed	18,231 FPM	18,272 FPM	18,266 FPM	18,266 FPM
Blade Overlap	1-1/2"	1-1/2"	1-1/2"	1-1/2"
Blade Uplift	Parallel	Parallel	Parallel	Parallel
Driveline Size	ASAE Cat 3	ASAE Cat 3	ASAE Cat 3	ASAE Cat 3
Front Roller (optional)	3" x 5"	3" x 5"	3" x 5"	3" x 13"
Discharge	Rear	Rear	Rear	Rear
Deck Thickness	7ga	7ga	7ga	7ga
Tires	3-1/4 x 10 Solid	3-1/4 x 10 Solid	4 x 10 Solid	5 x 13 Solid
Belts	(1) "B" Size Aramid Cord	(1) "B" Size Aramid Cord	(1) "B" Size Aramid Cord	(2) "B" Size Aramid Cord
Belt Adjustment	Spring-Loaded Idler	Spring-Loaded Idler	Spring-Loaded Idler	Spring-Loaded Idler
Gearbox	45 HP	45 HP	55 HP	55 HP
Approx. Weight	672 lbs	730 lbs	954 lbs	1190 lbs
Warranty	1-Year Limited Warranty with a 5-Year Limited Gearbox Warranty			



BUSH HOG®
Performance You Can Count On™

Bush Hog®, Inc.
2501 Griffin Ave., Selma, AL 36703
334.874.2700
www.bushhog.com